



Lighting design Co. & LED LUMINAIRES


Indoor products

Downlights & Recessed Trimlesses

چراغ های سقفی توکار DOWN LIGHT

چراغ های سقفی توکار دامنه گسترده ای از محصولات را برای نورپردازی محیط های مختلف با شرایط متفاوت در برمیگیرد. عدم ایجاد خیرگی به دلیل تو رفتگی منبع نور، و نیز سطح تیره رفلکتور داخل چراغ و هم چنین تنوع در فرم ظاهری برای هماهنگی با محیطها و کاربری های مختلف، از ویژگی های برجسته این نوع محصولات است.

در این سری از نسل جدید، آل ای دی هایی با راندمان بالا استفاده شده است که این امر به ایجاد نورپردازی دلنشین تر با طیف کامل رنگ های قابل تشخیص (CRI بالا) و کاهش انرژی انجامیده است.




بوتیک لومیر، مجتمع تجاری پالادیوم، تهران




DARK LIGHT-2L

Code: DL 2L
Luminous flux: 1800 lm
Color temperature: 3000K, 4000K
Wattage: 20 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Cut Size: ∇ 265X95 mm




Color: ☐ ☐




DARK LIGHT-2SP (SPEAKER BUILT IN)

Code: DL 2SP
Luminous flux: 1800 lm
Color temperature: 3000K, 4000K
Wattage: 20 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Cut Size: ∇ 265X95 mm




Color: ☐ ☐



DARK LIGHT-109S

Code: DL109S
Luminous flux: 900 lm
Color temperature: 3000K, 4000K
Wattage: 10 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Cut size: ∇ 95X95 mm



Color: ☐ ☐




DARK LIGHT-105S

Code: DL105S
Luminous flux: 540 lm
Color temperature: 3000K, 4000K
Wattage: 6 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Cut Size: ∇ 75X75 mm



Color: ☐ ☐



DARK LIGHT-2

Code: DL 2
Luminous flux: 1800 lm
Color temperature: 3000K, 4000K
Wattage: 20 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Cut Size: ∇ 175X95 mm



Color: ☐ ☒





DARK LIGHT-105 CW

Code: DL105CW
Luminous flux: 540 lm
Color temperature: 3000K, 4000K
Wattage: 6 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Cut Size: ∇ Ø73 mm



Color: ☐ ☒






DARK LIGHT-3

Code: DL3
 Luminous flux: 2700 lm
 Color temperature: 3000K, 4000K
 Wattage: 30 W
 Voltage: 220 VAC
 CRI>80
 Installation: Recessed
 Cut Size: ∇ 265X95 mm



Color: ☐ ☒




DARK LIGHT-4


Code: DL4
 Luminous flux: 3600 lm
 Color temperature: 3000K, 4000K
 Wattage: 40 W
 Voltage: 220 VAC
 CRI>80
 Installation: Recessed
 Cut Size: ∇ 175X175 mm



Color: ☐ ☒



DARK LIGHT-109M




Code: DL109M
Luminous flux: 900 lm
Color temperature: 3000K, 4000K
Wattage: 10 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Cut Size: Ø 95mm



Color:

DARK LIGHT-105M




Code: DL105M
Luminous flux: 540 lm
Color temperature: 3000K, 4000K
Wattage: 6 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Cut Size: Ø 70mm



Color:

DARK LIGHT-109C




Code: DL109C
Luminous flux: 900 lm
Color temperature: 3000K, 4000K
Wattage: 10 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Cut Size: Ø 95 mm



Color:

DARK LIGHT-105C



Code: DL105C
Luminous flux: 540 lm
Color temperature: 3000K, 4000K
Wattage: 6 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Cut Size: Ø 75 mm



Color:



HERA- 002

Code: H 002
 Luminous flux: 630/1080 lm
 Color temperature: 3000K, 4000K
 Wattage: 7 W/12 W
 Voltage: 220 VAC
 CRI>80
 Installation: Recessed
 Body: Aluminum
 Cut Size: $\varnothing$ 70 mm



Color: ☐ ☒





HERA-1406

Code: H 1406
 Luminous flux: 540 lm
 Color temperature: 3000K, 4000K
 Wattage: 6 W
 Voltage: 220 VAC
 CRI>80
 Installation: Recessed
 Body: Aluminum
 Cut Size: $\varnothing$ 70 mm




Color: ☐ ☒ ☐ ☐




LED PANEL (9X9 Cm)

Code: LP 9x9
Luminous flux: 695 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 8 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Aluminum
Cut Size: ∇ 70X70mm




LED PANEL (12X12 Cm)

Code: LP 12x12
Luminous flux: 1338 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 16 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Aluminum
Cut Size: ∇ 99X99 mm




LIANA 505 P


Code: L505P
Luminous flux: 450 lm
Color temperature: 3000K, 6000K
Wattage: 5 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Aluminum
Cut Size: ∇ Ø 45 mm



MACROSOL-N


Code: Macrosol-n
Luminous flux: 210 lm
Color temperature: 3000K, 4000K, 6500K
Wattage: 3 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Aluminum
Cut Size: ∇ Ø 33 mm






LED PANEL (60X60 Cm)

Code: LP 60x60
Luminous flux: 3980 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 48 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Aluminum




LED PANEL (30X120 Cm)

Code: LP 30x120
Luminous flux: 3980 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 48 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Aluminum



LED PANEL (22X22 Cm)

Code: LP 22x22
Luminous flux: 1980 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 22 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Aluminum
Cut Size: 207x207 mm





LED PANEL (30X30 Cm)

Code: LP 30x30
Luminous flux: 1660 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 20 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Aluminum




چراغ های سقفی توکار - بدون لبه TRIMLESS

ایجاد فرم زیبا و هماهنگ با طراحی محیط، بدون دیده شدن لبه چراغ، به دست آوردن نوری زیبا، دلنشین و بدون ایجاد خیرگی از ویژگی های برجسته این دسته چراغ هاست. پس از اتمام مراحل نصب درزهای موجود بین چراغ و سقف کاملاً پوشانده شده و چراغ به عنوان قسمتی از سقف دیده خواهد شد. همچنین در صورت نیاز، منبع نور (لامپ) به راحتی قابل تعویض است.



ساختمان اداری حکیم اعظم، شیخ بهایی، تهران



TRIMLESS-001

Code: TR001
 Luminous flux: 540 lm
 Color temperature: 3000K, 4000K
 Wattage: 6 W
 Voltage: 220 VAC
 CRI>80
 Installation: Recessed
 Body: Aluminum
 Cut Size: $\varnothing$ 80 mm



Color: ☐ ☒ ☐ ☐




TRIMLESS-002

Code: TR002
 Luminous flux: 540 lm
 Color temperature: 3000K, 4000K
 Wattage: 6 W
 Voltage: 220 VAC
 CRI>80
 Installation: Recessed
 Body: Aluminum
 Cut Size: 175X175 mm



Color: ☐ ☒




TRIMLESS-003

Code: TR003
Luminous flux: 540 lm
Color temperature: 3000K, 4000K
Wattage: 6 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Aluminum
Cut Size: $\nabla \nabla \nabla$ 80X80 mm



Color: ☐ ☐ ☐ ☐




TRIMLESS-004

Code: TR004
Luminous flux: 540 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 6 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Gybsum
Cut Size: $\nabla \nabla \nabla$ 103X103 mm






TRIMLESS-005



Code: TR005
 Luminous flux: 1080 lm
 Color temperature: 3000K, 4000K, 6000K
 Wattage: 12 W
 Voltage: 220 VAC
 CRI>80
 Installation: Recessed
 Body: Gybsum
 Cut Size: ∇ 193X123mm



TRIMLESS-006




Code: TR006
 Luminous flux: 1950 lm
 Color temperature: 3000K, 4000K
 Wattage: 30 W
 Voltage: 220 VAC
 CRI>90
 Installation: Recessed
 Body: Gybsum
 Cut Size: ∇ 327X47mm



TRIMLESS-007





Code: TR007
Luminous flux: 540 lm
Color temperature: 3000K, 4000K
Wattage: 6 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Gybsum
Cut Size: ∇ 123X123mm



TRIMLESS-008




Code: TR008
Luminous flux: 540 lm
Color temperature: 3000K, 4000K
Wattage: 6 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Gybsum
Cut Size: ∇ 123X123mm



TRIMLESS-009





Code: TR009
Luminous flux: 540 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 6 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Gybsum
Cut Size: ∇ $\varnothing$ 230 mm







TRIMLESS-010

Code: TR010
Luminous flux: 540 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 6 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Gybsum
Cut Size: $\nabla \nabla \nabla$ 123X123mm




PANIZ-S


Code: p-s
Luminous flux: 540 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 6 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Gybsum
Cut Size: $\nabla \nabla \nabla$ 100X100mm



TRIMLESS-011

Code: TR011
Luminous flux: 1080 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 12 W
Voltage: 220 VAC
CRI>80
Installation: Recessed
Body: Gybsum
Cut Size: $\nabla \nabla \nabla$ 217X120mm





PANIZ-L-M

Code: p-l-M
Luminous flux: 220 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 3 W
Voltage: 220 VAC
Installation: Recessed
Body: Gybsum
Cut Size: $\nabla \text{ } \text{ } \nabla$ 85X170mm



PANIZ-L-B

Code: p-l-B
Luminous flux: 220 lm
Color temperature: 3000K, 4000K, 6000K
Wattage: 3 W
Voltage: 220 VAC
Installation: Recessed
Body: Gybsum
Cut Size: $\nabla \text{ } \text{ } \nabla$ 250X115mm



Head Office & Showroom

No.20,South Kaveh Blv, Sadr Highway, Tehran-IRAN.

Tel: +98 21 22 63 91 63

Website: www.fadco.ir